

Miracleclean EC-315

Liquid Electrocleaner Component

Technical Data

GENERAL DESCRIPTION

Miracleclean EC-315 is a concentrated liquid product for use with **Miracleclean LB-620** as an excellent anodic electrocleaner for steel parts. **Miracleclean EC-315** is excellent for removal of oil and smut.

NORMAL USE

Concentration of Miracleclean EC-315	3 – 8% by volume
Concentration of Miracleclean LB-620	5 – 20%
Normal Ratio of Miracleclean LB-620 to Miracleclean EC-315	3 to 1
Temperature	140 – 190° F
Current	30 – 100 amps per ft ²
Polarity of Part	Anodic (Positive)
Time	0.5 to 3 minutes

Note: Make maintenance addition at the same ratio as the initial charge of the tank.

ADVANTAGES

1. Water based product so no dusting or noxious fumes to breathe.
2. Biodegradable.
3. Long tank life.
4. Useful over a wide range of applications and operating conditions.
5. Liquid product makes automatic chemical feed easy.

NORMAL CONTROL

Analytical Method (Equipment available from Chautauqua Chemicals Co.)

HANDLING AND SAFETY CONSIDERATIONS

Consult MSDS sheet on this product for handling considerations, hazard information, and first aid procedures.

OTHER INFORMATION

No warranty, expressed or implied of merchantability fitness for a particular purpose or otherwise, is made. Buyer assumes all risk of use, storage and handling. Chautauqua Chemicals Company, Inc. shall not be made liable for any incidental or consequential damages arising directly or indirectly in connection with the purchase, storage, handling or disposal of this product.

TDS Number:
Revision Date:

50647C
July 22, 2014

