

QC 1130B

Burnishing Compound
Technical Data

GENERAL DESCRIPTION

QC 1130B is a tumbling compound which has excellent burnishing and rust inhibiting properties. This product allows for single step burnish and rust inhibit.

QC 1130B may be used in vibratory, conventional barrel, or new high speed mass finishing operations.

QC 1130B is designed for ferrous alloys.

NORMAL USE

As a tumbling compound, **QC 1130B** can be used either in batch or continuous tumbling systems.

Use between 1 to 4 ounces per gallon of water (1 to 2 ounces per gallon is typical).

Flow-through operation is recommended for best results.

ADVANTAGES

1. Medium foaming compound.
2. Environmentally friendly.
3. Excellent burnishing capabilities on steel substrates.
4. Liquid product makes automatic feeding easy.

HANDLING AND SAFETY CONSIDERATIONS

Consult product safety data sheet for handling considerations, hazard information, and first aid procedures.

OTHER INFORMATION

No warranty, expressed or implied of merchantability fitness for a particular purpose or otherwise, is made. Buyer assumes all risk of use, storage and handling. Chautauqua Chemicals Company, Inc. shall not be made liable for any incidental or consequential damages arising directly or indirectly in connection with the purchase, storage, handling or disposal of this product.

TDS Number:
Revision Date:

53183A
February 24, 2016

